



CREPIFLEX

FLEXIBLE GRANULAR FILLING ROUGHCAST

la marque
du bâtiment

1. PRESENTATION

One-component **sealant** made with **acrylic copolymers and silicate additives**

Ready to use and packaged as a **cartridge**, its structured and relief surface restores the original appearance of granular materials on your façades.

2. AREAS OF APPLICATION

- **Finishing and repair joints, and filling of cracks** on roughcast.
- **Jointing** between wall panels for prefabricated structures and renovation.
- Finishing joint between ceilings and walls.
- **Grouting** of facing bricks.

4. CHARACTERISTICS

Type: Plasto-elastic – aqueous dispersion.

Density: 1.80 g/ml

Dry content: 91%

Extrudability: 500 g/min (Ø 3 mm – 6.3 bar)

Creep: < 2 mm (ISO 7390)

Shore A hardness: 28° (DIN 53505)

Elongation at failure: 50% (DIN 53504)

Permanent deformation: 10% maximum allowable

Temperature resistance: -20°C to +75°C

Application temperature: +5°C to +40°C

Smoothing time: 5 min (23°C and 50% RH)

Cross-linking time: Depends on the temperature, the size of the joints and the ambient weather conditions

3. INSTRUCTIONS

Substrates: Surfaces must be clean, dusted, free of grease and loose particles. First cover very porous substrates with an acrylic sealant solution diluted with twice its volume of water.

Painting: After complete drying. Cracking may appear on heavily loaded acrylic paints. Preliminary compatibility tests are recommended.

Joint width: 4 mm minimum, 25 mm maximum.

Cleaning of fresh sealant: water.

Washing of hands: soapy water.

Packaging

Colour: White

Packaging: 310 ml cartridges

5. RECOMMENDATIONS

Avoid smoothing the sealant so as to preserve its granular appearance. Smooth out the sealant using a slightly damp sponge. Dab or use a roughcast roller to accentuate the relief.

Caution:

Do not expose the joint to water within 5 hours of its application.

Do not use on surfaces highly exposed to water or weathering.

Do not use on PE, PP, Teflon® and bituminous materials.

Protect from rain during the drying process.

Do not use for prolonged contact with water.

6. ADVANTAGES

- Strong adhesion on most construction substrates.
- Good compatibility with standard paints.
- Non-corrosive to metals.
- Excellent resistance to ageing.
- Applications indoors and outdoors.
- Frost-proof.

7. SAFETY OF USE

Follow usual occupational hygiene procedures.

Protect from rain during the drying process.

Do not use for prolonged contact with water.

Perform a preliminary compatibility test before painting over.

Shelf life: 12 months in unopened original packaging, kept in a dry location between +5°C and +25°C.

The details provided in this Data Sheet are given in good faith, for information purposes only. They shall not in any case constitute a guarantee on our part, or engage our responsibility when using our products. This Data Sheet supersedes all previous versions. Compagnie France Chimie reserves the right to make changes to its products and to this data sheet without prior notice. Our clients shall ensure, before any implementation, that these instructions have not been replaced by a more recent version that takes into account new technical data.

Product solely intended for professional use.

EURO DORTHZ PRODUCTION

42/44 rue Georges Besse — 63100 Clermont-Ferrand — FRANCE
Tel. +33 (0) 4 73 14 40 40 / Fax +33 (0) 4 73 14 40 44
Website: www.dorthz.com

