



la marque  
du bâtiment

# AERO EUROJET

## SILICONE FREE ANTI-ADHESIVE FLUID

### 1. PRESENTATION

Fluid **sprayed** to produce a **colourless**, chemically **inert** and thermally **stable** film, the low surface tension of which allows for a quick, wide spread over the surfaces thus rendered **anti-adhesive** et **hydrophobic**.

### 2. ADVANTAGES

- Stable from -40°C to +200°C.
- Colourless and virtually odourless film.
- **Repels moisture.**
- High anti-adhesive capacity.
- Gives a like-new appearance to plastic trims.

### 3. AREAS OF APPLICATION

- **Slip agent for joinery.**
- Lubrication of small mechanisms.
- **Waterproofing of fabric, leather, suede garments.**
- Plastics renovator.
- **Protection of door seals and vehicle locks against freezing.**
- **Protection of the ignition circuit of vehicles against moisture.**

### 4. INSTRUCTIONS

Shake before use.

Very easy to spray thanks to the aerosol packaging.

The film must be sprayed onto extremely clean surfaces only after all traces of grease have been removed using a suitable solvent.

Spray from a distance of 25 - 30 cm.

Wipe immediately using a soft cloth, evenly and without rubbing.

The film forms instantly.

The spray frequency depends on the severity of the work required.

### 5. CHARACTERISTICS

Appearance:	liquid
Density:	< 1
Flash point:	< 0°C
Aerosol can capacity:	650 ml
Net volume:	400 ml

Preserves the ozone layer

*(For more information, please refer to paragraph 9 of the safety data sheet).*

### 6. SAFETY OF USE

- See the product's Safety Data Sheet at [www.quickfds.fr](http://www.quickfds.fr).
- Do not use near a paint facility (anti-adhesive capacity).
- Pressurized container: protect from direct sunlight and extreme temperatures.
- Do not pierce or burn, even after use.
- Do not spray on a naked flame or any incandescent material.

*The details provided in this Data Sheet are given in good faith, for information purposes only. They shall not in any case constitute a guarantee on our part, or engage our responsibility when using our products. This Data Sheet supersedes all previous versions. Compagnie France Chimie reserves the right to make changes to its products and to this data sheet without prior notice. Our clients shall ensure, before any implementation, that these instructions have not been replaced by a more recent version that takes into account new technical data.*

**Product solely intended for professional use.**

#### EURO DORTHZ PRODUCTION

42/44 rue Georges Besse — 63100 Clermont-Ferrand — FRANCE  
Tel. +33 (0) 4 73 14 40 40 / Fax +33 (0) 4 73 14 40 44  
Website: [www.dorthz.com](http://www.dorthz.com)

