

# AERO EUROLEC HT

## DIELECTRIC SAFETY SOLVENT – POWER OFF

### 1. PRESENTATION

**AERO EUROLEC HT** is a dry and ultra-powerful solvent, with very quick drying and evaporation properties.

Ideal for cleaning electrical and electronic parts powered off, as well as extremely dirty mechanical parts.

Compatible with most metallic, plastic, elastomer substrates.

Allows cleaned parts free of harmful residues and films to be quickly returned to service.

Removes the need for compressed air cleaning.

### 2. ADVANTAGES

- Very easy to spray thanks to the aerosol packaging.
- Simple, quick and economical application.
- Leaves no residues or traces after drying, and leaves surfaces clean.
- Allows the cleaning and deoxidising of equipment without disassembly.
- Its low surface tension allows very high penetration in hard to reach places.
- Does not disrupt circuits, but restores electric constants.
- No action on metals (steel, copper), plastics, screen printing markings, paint, etc...
- Does not attack insulating varnishes.
- Dielectric: dielectric strength > 21 kV.

### 3. AREAS OF APPLICATION

- Cleaning, degreasing and removal of:
  - Dust, oil, wax, grease, paraffin, carbon residues, rubber marks, release agent, polish, etc. on:
    - Oil burners.
    - Potentiometers, switches.
    - Electrical contacts in electric and electronic circuits.
    - Mechanical parts.
    - Heat engines, carburettors, injectors, bearings, brakes.
    - Worksite equipment, tools (drill, jackhammer, etc.).
    - Welding flux, textiles.
    - Small mechanisms (clockwork), etc.

### 4. INSTRUCTIONS

Shake the aerosol can before use.

Hold the aerosol can upright.

Spray in short bursts directly on the areas to be treated. The product acts immediately.

Repeat the process if necessary.

### 5. CHARACTERISTICS

Appearance:	liquid
Density:	< 1
Propellant	Nitrous oxide
Aerosol can capacity:	650 ml
Net volume:	400 ml

Preserves the ozone layer

*(For more information, please refer to paragraph 9 of the safety data sheet).*

# AERO EUROLEC HT

DIELECTRIC SAFETY SOLVENT – POWER OFF

## 6. SAFETY OF USE

- See the product's Safety Data Sheet at [www.quickfds.fr](http://www.quickfds.fr).
- On oil burners: protect the photoelectric cell.
- Follow the instructions relating to the storage and handling of gas-filled pressure vessels.
- Aerosol container: do not pierce or burn, even after use.
- Warning: highly flammable product, maintain aeration or adequate ventilation in the room. Do not use on energised equipment; do not power up until after fumes have evaporated / been removed.
- Substrates: first check the tolerance of the substrate (or protective insulating varnish) with the product.

*The details provided in this Data Sheet are given in good faith, for information purposes only. They shall not in any case constitute a guarantee on our part, or engage our responsibility when using our products. This Data Sheet supersedes all previous versions. Compagnie France Chimie reserves the right to make changes to its products and to this data sheet without prior notice. Our clients shall ensure, before any implementation, that these instructions have not been replaced by a more recent version that takes into account new technical data.*

**Product solely intended for professional use.**

**EURO DORTHZ PRODUCTION**

42/44 rue Georges Besse — 63100 Clermont-Ferrand — FRANCE  
Tel. +33 (0) 4 73 14 40 40 / Fax +33 (0) 4 73 14 40 44  
Website: [www.dorthz.com](http://www.dorthz.com)

