

la marque du bâtiment

# AERO GRAISSE X-TREME

#### LITHIUM COMPLEX GREASE

### 1. PRESENTATION

As a genuine long-lasting grease, AERO GRAISSE X-TREME is a very high performance, extreme pressure lithium complex grease packaged as a 650 ml aerosol can, making it an all-purpose grease that allows the spacing of lubrication, as well as faultless and permanent protection against wear, corrosion, rust.

# 2. ADVANTAGES

- Excellent natural adhesion to metal.
- Very low resistive torque.
- Shear strength, low consistency variation even after intensive work.
- Excellent water resistance.
- Extreme pressure and anti-wear properties.
- Protection against moisture and corrosion.
- 3. AREAS OF APPLICATION
- Bearings of all types subjected to any engine speed up to 10,000 revolutions per minute, over very wide temperature ranges, from -30℃ to +150℃.
- Ring gears of concrete mixers
- Hydraulic jacks, lifting equipment.

- Stable consistency and lubricity over a wide temperature range.
- Oxidation resistance ensuring the preservation of properties over a long period, typically 3 to 5 times that of a good multi-service grease.
- Journal bearings.
- Universal joints for vehicles and professional equipment.
- Fifth wheel for tractors, semi-trailers, etc.

# 4. INSTRUCTIONS

Clean the parts to be treated before application.

Shake the aerosol can vigorously until the agitator ball is loose.

Spray on the parts to be treated.

Use the capillary tube for hard to reach places.

Purge the aerosol can upside down after use.

## 5. CHARACTERISTICS

Appearance: thin liquid

Density: < 1Flash point ( $^{\circ}$ C):  $< 0^{\circ}$ C Aerosol can capacity: 650 ml Net volume: 500 ml

(For more information, please refer to paragraph 9 of the safety data sheet).

### 6. SAFETY OF USE

- See the product's Safety Data Sheet at www.quickfds.fr.
- Dangerous, contains trichlorethane III.
- Pressurized container: protect from direct sunlight and extreme temperatures.
- Do not pierce or burn, even after use.
- Do not spray on a naked flame or any incandescent material.

The details provided in this Data Sheet are given in good faith, for information purposes only. They shall not in any case constitute a guarantee on our part, or engage our responsibility when using our products. This Data Sheet supersedes all previous versions. Compagnie France Chimie reserves the right to make changes to its products and to this data sheet without prior notice. Our clients shall ensure, before any implementation, that these instructions have not been replaced by a more recent version that takes into account new technical data.

Product solely intended for professional use.

