

ARMADORTHZ

REINFORCEMENT OF JOINTS AND CRACKS

1. PRESENTATION

ARMADORTHZ is a non-woven polyester band used for bridging joints and cracks between two layers of **ETANCH TERR**, **PAINT F ELASTANCH**, **IMPER T.B.L.** or **ETANCH MAX** waterproof coating.

2. ADVANTAGES

- 100% Polyester. Imputrescible, très élastique.
- **ARMADORTHZ** is very elastic and works the same way in all directions, unlike glass fabrics.
- High resistance to breaking, punching and tearing.
- Resists to instant substrate cracking, even at low temperatures.

3. AREAS OF APPLICATION

- Broken tiles and slates.
- Chimney stacks, fillets.
- Ridges, edges, gutters.
- Acroterion, joints for prefabricated structures.

4. INSTRUCTIONS

Substrate preparation:

They must be brushed, dusted. Loose parts must be removed. If necessary, strip paints, concrete, mortar and asphalt coating.

Remove moss, algae and lichen using **MOUSSTOP 4 PLUS**.

For porous substrates, apply an undercoat of **ETANCH TERR**, **PAINT F ELASTANCH**, **IMPER T.B.L.** or **ETANCH MAX** diluted to 50% with water. Leave to dry for 2 hours.

Implementation:

Apply a generous coat of **ETANCH TERR**, **PAINT F ELASTANCH**, **IMPER T.B.L.** or **ETANCH MAX** undiluted.

Place the reinforcement band over the fresh product using a brush or a spatula, making sure it is well impregnated without forming any creases or bubbles. Smooth carefully from the inside to the outside.

Leave to dry for 24 hours, then completely cover the repair using **ETANCH TERR**, **PAINT F ELASTANCH**, **IMPER T.B.L.** or **ETANCH MAX** undiluted.

5. CHARACTERISTICS

Spread :	50g/m ²
Elongation at failure :	⇒ 40% ↑29%
Tensile strength:	⇒ 49N ↑47N

6. SAFETY OF USE

- Not suitable for use with coatings or mortars.

The details provided in this Data Sheet are given in good faith, for information purposes only. They shall not in any case constitute a guarantee on our part, or engage our responsibility when using our products. This Data Sheet supersedes all previous versions. Compagnie France Chimie reserves the right to make changes to its products and to this data sheet without prior notice. Our clients shall ensure, before any implementation, that these instructions have not been replaced by a more recent version that takes into account new technical data.

Product solely intended for professional use.