



la marque  
du bâtiment

# PAINT B LASURE



FONGICIDAL INSECTICIDAL WATER-REPELLENT SATIN WOOD STAIN

AFNOR CLASSIFICATION, FRENCH STANDARD NFT 36 005 FAMILY 1 CLASS 4A

## 1. PRESENTATION

**PAINT B LASURE** is a satin wood stain that comes in the form of a ready to use (thixotropic) semi gel that contains microporous alkyd resins resulting from the latest research in the field of ageing of polymers, and combines great ease of application, very high UV resistance and unique wood protection.

## 2. ADVANTAGES

**PAINT B LASURE** is used to decorate and protect exterior and interior trims made of exotic woods, both new and old, against aggressions.

- High covering capacity.
- Gelled, does not drip (facilitates its application on vertical surfaces) and easily penetrates wood.
- Available in several colours, all miscible with one another.
- Once applied, it provides a nice finish while preserving the natural structure of wood, especially the grain.
- Offers excellent protection for long-term treatment: up to 6 years both indoors and outdoors, even for substrates facing west.
- Preventive insecticide and fungicide for wood surfaces.
- Anti-UV: contains agents to improve the resistance to sunlight (even with the colourless option) of scavengers that destroy the free radicals responsible for the accelerated ageing of wood.
- Water-repellent (effective outdoors) that protects the substrates while allowing them breathing.
- All wood varieties exposed to urban, rural and industrial atmospheres.
- No risk of blistering or flaking.

## 3. AREAS OF APPLICATION

- Indoor and outdoor use.
- All wood varieties, both new and old.
- Restoring the original appearance of wood.
- Protection of substrates against the harmful effects of UV rays, snow, rain, moonlight.
- Decoration of wood, frames, beams, cladding, shutters, gates, joinery, panelling, garden sheds, benches, etc.

## 4. INSTRUCTIONS

### Substrate preparation:

Substrates must be sound, clean, free of oil and grease.

With woods having moisture contents of less than 18% on the outside and 12% on the inside.

### Preparatory work:

- Remove Laitances using **DECAP CIM SF**.  
Traces of oil and grease using **NETT M**.  
Algae, moss, lichen using **MOUSSTOP 4 PLUS** or **15 PLUS**.  
Old coats of loose paint, wood stain and varnish using **DECAP ALL**.  
Loose particles (scraping), dust (brushing).  
Old waxes, paraffins using **NETT PROCLEAN**.

EURO DORTHZ PRODUCTION

42/44 rue Georges Besse — 63100 Clermont-Ferrand — FRANCE  
Tel. +33 (0) 4 73 14 40 40 / Fax +33 (0) 4 73 14 40 44  
Website: [www.dorthz.com](http://www.dorthz.com)





la marque  
du bâtiment

# PAINT B LASURE



FONGICIDAL INSECTICIDAL WATER-REPELLENT SATIN WOOD STAIN  
AFNOR CLASSIFICATION, FRENCH STANDARD NFT 36 005 FAMILY 1 CLASS 4A

Traces of fat (nicotine, pollution) using **NETT PROCLEAN**.

On wood bleached or greyed by weathering, apply **DEGRISANT BOIS** or **NETT SUPPORT**.

- Rinse with water.
- Exuding exotic woods: degrease using **NETT BROSS**, replace wiping cloths often. (Afzelia: wash with ammonia).
- Woods already attacked or suspicious (xylophagous insects or fungi) shall be pretreated using **XYLO M.S.B**.
- Cover the heads of nails or screws with **POLYPLAST**.
- Wait for **complete drying** before applying **PAINT B LASURE**.

Precautions:

For some varieties that contain antioxidants or non-set resins (iroko, doussie, teak, pine, larch, etc.), perform a test beforehand and if necessary, use the appropriate treatment.

On tropical woods, choose a colour close to that of the wood variety.

We cannot be held responsible for the non-holding, bonding or drying of **PAINT B LASURE** on silicone substrates which have been subject to a pre-treatment.

On surfaces with a slight gradient, the resistance of the product to weathering is greatly reduced.

*These recommendations cannot replace the appropriate determination of the nature and condition of the substrates to be painted.*

- Do not apply on frozen or thawing substrates, or those likely to freeze.
- Do not apply on hot substrates and in threatening weather.
- Beware of the dew point.

Implementation:

**PAINT B LASURE** is ready to use.

Shake well before use and during use.

	INTERIOR WOOD	EXTERIOR WOOD
NEW SUBSTRATE	Apply 2 coats. Light sanding between coats will allow for a better finish.	Apply 3 coats. The first coat shall be diluted to 20% with <b>NETT BROSS</b> . Light sanding between coats will allow for a better finish.
MAINTENANCE	Apply one coat after a light sanding.	

**EURO DORTHZ PRODUCTION**

42/44 rue Georges Besse — 63100 Clermont-Ferrand — FRANCE  
Tel. +33 (0) 4 73 14 40 40 / Fax +33 (0) 4 73 14 40 44  
Website: [www.dorthz.com](http://www.dorthz.com)





la marque  
du bâtiment

# PAINT B LASURE



FONGICIDAL INSECTICIDAL WATER-REPELLENT SATIN WOOD STAIN

AFNOR CLASSIFICATION, FRENCH STANDARD NFT 36 005 FAMILY 1 CLASS 4A

## Application:

Application conditions	: As per standard NF P 74-201-1
Application temperature	: Between +10°C and +35°C
Hygrometry	: Outdoors, ≤ 80% relative humidity : Indoors, ≤ 65% relative humidity
Application equipment	: Brush, roller, airless spray gun, soaking
Thinner	<b>NETT BROSS</b>
Cleaning of the equipment	: <b>NETT BROSS</b> (do not allow to dry) : <b>DECAP ALL</b> if the product is dry

## 5. CHARACTERISTICS

Packaging	: Ready to use
Appearance in container	: Semi-gelled liquid
Film appearance	: Satin
Density	: 0.89 ±0.05 g.cm <sup>-3</sup>
Dry content	: 38 ±2% by weight
VOC (Directive 2004/42/EC)	: EU limit value for this product (cat. A/f)*: 700 g/L (2010). This product contains 650g/L maximum.
Yield	: 15 m <sup>2</sup> /L per coat depending on the porosity of the substrate. : I.e. 1 L for 6 to 7 m <sup>2</sup> with 2 coats depending on the wood variety
Drying (20°C – 65% RH)	: Touch dry in 6 hours
Coating over	: 18 hours
Colours	: As per <b>PAINT B LASURE</b> colour chart
Shelf life	: 1 year in its unopened original packaging

(For more information, please refer to paragraph 9 of the safety data sheet).

## 6. SAFETY OF USE

- See the product's Safety Data Sheet at [www.quickfds.fr](http://www.quickfds.fr).
- Store away from frost.
- Does not meet food-grade coating standards.
- Do not apply on parquet or wooden floors.

### EURO DORTHZ PRODUCTION

42/44 rue Georges Besse — 63100 Clermont-Ferrand — FRANCE  
Tel. +33 (0) 4 73 14 40 40 / Fax +33 (0) 4 73 14 40 44  
Website: [www.dorthz.com](http://www.dorthz.com)





la marque  
du bâtiment

# PAINT B LASURE



FONGICIDAL INSECTICIDAL WATER-REPELLENT SATIN WOOD STAIN  
AFNOR CLASSIFICATION, FRENCH STANDARD NFT 36 005 FAMILY 1 CLASS 4A

(1) In accordance with standard NF T 34-002, the colourless option cannot be used alone despite being treated against UV rays. It is intended for colour dilution.

(2) Resistance on low permeability wood varieties (e.g. oak, teak, iroko, chestnut...) will be reduced. A maintenance coat every 3 years may be useful depending on the wood variety and exposure.

## PAINT B LASURE colour chart:

Colourless



Dark oak



Medium oak



Light oak



Chestnut

The details provided in this Data Sheet are given in good faith, for information purposes only. They shall not in any case constitute a guarantee on our part, or engage our responsibility when using our products. This Data Sheet supersedes all previous versions. Compagnie France Chimie reserves the right to make changes to its products and to this data sheet without prior notice. Our clients shall ensure, before any implementation, that these instructions have not been replaced by a more recent version that takes into account new technical data.

**Product solely intended for professional use.**

**EURO DORTHZ PRODUCTION**

42/44 rue Georges Besse — 63100 Clermont-Ferrand — FRANCE  
Tel. +33 (0) 4 73 14 40 40 / Fax +33 (0) 4 73 14 40 44  
Website: [www.dorthz.com](http://www.dorthz.com)

