

la marque du bâtiment

# PROTEG FILM RENFORCE

## PROTECTIVE FILM WITH ADHESIVE EDGE

#### 1. PRESENTATION

**PROTEG FILM RENFORCE** is designed to protect stairs and floors during painting work. For safety purposes, **PROTEG FILM REINFORCE** includes a special non-slip film.

#### 2. ADVANTAGES

- Electrostatic plastic film.
- Quick and easy installation.
- Good adhesion.
- Easy to strip.

#### 3. AREAS OF APPLICATION

The large protective width provides effective protection to the following elements during painting or sprayed coating work:

- Stairs.
- Parquet floors, tiling, enamel, etc.
- With reinforced non-slip film.

#### 4. INSTRUCTIONS

Applied manually on clean and dry substrates.

Stick the adhesive tape and roll out the electrostatic film. At the bottom and on the sides, use **PROTEG CACHE VITE** for a better hold (In the case of paint applied using a spray gun or in windy conditions).

#### 5. CHARACTERISTICS

Dimensions Tape quality Film quality Suitable surface Leaves no deposit upon removal UV resistance

### : 1600 mm x 15 m *Code 624* : Cloth tape

- : HDPE film (green)
- : Smooth / rough
- : Up to 3 weeks : yes

#### 6. SAFETY OF USE

• Store away from moisture.

The details provided in this Data Sheet are given in good faith, for information purposes only. They shall not in any case constitute a guarantee on our part, or engage our responsibility when using our products. This Data Sheet supersedes all previous versions. Compagnie France Chimie reserves the right to make changes to its products and to this data sheet without prior notice. Our clients shall ensure, before any implementation, that these instructions have not been replaced by a more recent version that takes into account new technical data.

#### Product solely intended for professional use.



**EURO DORTHZ PRODUCTION** 42/44 rue Georges Besse — 63100 Clermont-Ferrand — FRANCE Tel. +33 (0) 4 73 14 40 40 / Fax +33 (0) 4 73 14 40 44 Website: <u>www.dorthz.com</u>