



la marque
du bâtiment

AERO PAINT TRACAGE SOL



1. PRESENTATION

AERO PAINT TRACAGE SOL is a modified alkyd ground marking paint with an excellent covering capacity.

2. ADVANTAGES

- High resistance to water, cold temperatures, saline mist, air pollution and alkaline detergents.
- Dries quickly.
- High resistance to scratching and abrasion.
- Can be applied on many substrates (cement, asphalt, wood, etc.).
- Can be mounted on a trolley.

3. AREAS OF APPLICATION

Signal paint for use on cement, wood and asphalt coatings.

Recommended for road and safety signs, factories, stores and warehouses, parking lots, construction zones, sports fields, public works companies...

4. INSTRUCTIONS

Shake the aerosol can vigorously until the agitator ball is loose.

Use the aerosol can upside down with the two-finger diffuser for wider bands or with the diffuser when using the marking trolley.

Spray evenly.

Purge the aerosol upright after each use so as to leave the opening of the spray paint-free.

Leave to dry.

Application:

Application temperature	: Between +5°C and +50°C
Hygrometry	: Outdoors, ≤ 80% relative humidity
	: Indoors, ≤ 65% relative humidity
Yield	: 6.5 m ² per can of aerosol
	: 30 to 40 ml, European band size (width: 7 cm)
Drying	: Touch dry: 1 hour
	: Hard: 2 hours
	: Trafficable: 24 hours
Cleaning of the equipment	: NETT BROSS

5. CHARACTERISTICS

Appearance:	Gloss / satin paint
Colour:	White or yellow
Aerosol can capacity:	650 ml
Net volume:	500 ml

(For more information, please refer to paragraph 9 of the safety data sheet).



6. SAFETY OF USE

- See the product's Safety Data Sheet at www.quickfds.fr.
- Follow the instructions relating to the storage and handling of gas-filled pressure vessels.
- Always store the aerosol can upright.
- Keep out of reach of children.
- Do not apply on frozen grounds.

The details provided in this Data Sheet are given in good faith, for information purposes only. They shall not in any case constitute a guarantee on our part, or engage our responsibility when using our products. This Data Sheet supersedes all previous versions. Compagnie France Chimie reserves the right to make changes to its products and to this data sheet without prior notice. Our clients shall ensure, before any implementation, that these instructions have not been replaced by a more recent version that takes into account new technical data.

Product solely intended for professional use.

EURO DORTHZ PRODUCTION

42/44 rue Georges Besse — 63100 Clermont-Ferrand — FRANCE
Tel. +33 (0) 4 73 14 40 40 / Fax +33 (0) 4 73 14 40 44
Website: www.dorthz.com

