



la marque
du bâtiment

PROTEG PVC ORANGE

MULTI-PURPOSE PVC TAPE
HAND-CUTTABLE

1. PRESENTATION

PROTEG PVC ORANGE is a plasticised PVC tape coated with an adhesive rubber mass.

2. ADVANTAGES

- Economical.
- Very easy to **cut** by hand.
- Very easy to roll out.
- Very good adhesion.
- **Resistant** to water vapour and moisture, waterproof.
- Very good resistance to temperature (**-10°C to +70°C**) and weathering (rain, sunlight, cold).
- Does not break in cold temperatures.
- Long-lasting.
- Can be removed without leaving any trace.
- Conformable, it moulds itself well to the different shapes of substrates.
- Allows significant time savings.
- Can be used both indoors and outdoors.

3. AREAS OF APPLICATION

PROTEG PVC ORANGE can be applied on common building surfaces, either rough, smooth or porous, and is ideal for tasks such as:

- | | |
|-------------|--------------------------|
| - Repair, | - Protection, |
| - Marking, | - Support, |
| - Plugging, | - Holding of tarpaulins, |
| - Masking, | - Sealing. |

4. INSTRUCTIONS

Substrates must imperatively be dry, clean, sound and non-friable.

Brush very dusty substrates to remove loose particles.

Place the adhesive tape on the limits to be protected.

5. CHARACTERISTICS

Dimensions	: 50 mm x 33 m
Substrate	: PVC film
Adhesive	: Rubber
Overall thickness (µm)	: 100
Elongation at failure	: 170%
Adhesive strength on steel (N/cm)	: 0.8
Breaking load (N/cm)	: 21
Temperature resistance (°C)	: +70 °C



6. SAFETY OF USE

- Store in a temperate room.
- Always perform a preliminary test on paint and varnish.

The details provided in this Data Sheet are given in good faith, for information purposes only. They shall not in any case constitute a guarantee on our part, or engage our responsibility when using our products. This Data Sheet supersedes all previous versions. Compagnie France Chimie reserves the right to make changes to its products and to this data sheet without prior notice. Our clients shall ensure, before any implementation, that these instructions have not been replaced by a more recent version that takes into account new technical data.

Product solely intended for professional use.

EURO DORTHZ PRODUCTION

42/44 rue Georges Besse — 63100 Clermont-Ferrand — FRANCE
Tel. +33 (0) 4 73 14 40 40 / Fax +33 (0) 4 73 14 40 44
Website: www.dorthz.com

